

RED MANSIONS

红袖添香

MN626B

DESCRIPTION

一抹浓郁的红袖色，完美得呈大自然馈赠的石材本色，滚滚澎湃，像一座座红袖色的山，蜿蜒似发丝般细腻，渲染出别致的优雅气质，给人一种完美无瑕的质感。

The red color perfectly retains the primary tone of natural stone gifted by nature. Rolling and flowing, like mountains of red pomelo, the texture is as delicate as hair, rendering a unique elegance, giving people a kind of indifference.

SPECIFICATION

Size: 1200X2700X6mm
108" X 48" X 1/4"

卡拉纳 / Nonreflect Polished



ITEM NO.

MN626BP271206

FACE CONTINUITY



Scratch Resistant



Color Uniformity



Corrosion Resistance



Stain Resistant



Antimicrobial



Fire Resistant



Kitchen Cabinet



Vanity



Floor Wall



Furniture



Cover



TV Screen



Floor



Background Wall



Business Desk



Office Partition





Technical Features

技术特性

BEYOND ARTS FASHION

PHYSICAL PROPERTIES	REGULATION	REQUIRED VALUE	MOREROOM AVERAGE VALUES
DIMENSIONS	ISO 10545-2	± 0,6% max lenght and width	± 0,1% lenght and width
		± 5% max Thickness	± 5% Thickness
		± 0,5% max Linearity	± 0,1% Linearity
		± 0,5% max Wedging	± 0,1% Wedging
		± 0,5% max Warpage	± 0,2% Warpage
WATER ABSORPTION	ISO 10545-3	≤ 0,5 %	0.05% - 0.08%
MODULS OF RUPTURE (R)	ISO 10545-3	≥ 35 N/mm2	49 N/mm2
BREAKING STRENGHT (S)	ISO 10545-4	< 7,5mm = ≥ 700 N	Conforms
DEEP ABRASION RESISTANCE	ISO 10545-6	max 175 mm3	140 mm3
COEFFICIENT OF	ISO 10545-8	9x10-6°C-1	6,5x10-6°C-1
LINEAR THERMAL EXPANSION			
RESISTANCE TO THERMAL SHOCKS	ISO 10545-9	No sample must show alterations to surface	Available on request
FROST RESISTANCE	ISO 10545-12	No sample must show alterations to surface	Available on request
RESISTANCE TO CHEMICAL PRODUCTS	ISO 10545-13	Resistance to household chemicals and pool additives (min. class B)	A
		Resistance to acids and alkalis at low concentration	LB
		Resistance to highly concentrated acid and alkaline products	HB
STAIN RESISTANCE	ISO 10545-14	No sample must show alterations to surface	Stains removed by hot water (without detergent)
RESISTANCE TO LIGHT	DIN 51094	No sample must show alterations to surface	No change in brightness or colour of samples
FRICTION COEFFICIENT	BCRA REP CEC 6/81	0.40≤μ≤0.74	>0.4
REACTION TO FIRE	96/603/CE	Not applicable	A1 – A1FL
NOTES	*The slip resistance, static or dynamic coefficient of friction values shown in the catalog and in the Safe System table are to be considered purely indicative and not binding. Any specific need must be confirmed by us at the time of the order and in any case always before installation.		

Product performance

产品性能

Moreroom passes the certifications including ISO 9001 | ISO 50001 | ISO 14001 | EU EMAS | GREENGUARD | CCC | LEED | AEO, etc. From raw materials purchasing, monitoring of the production process, and the delivery of finished products, all the accusations of people, machines, materials, and procedures are strictly controlled in digitization, dramatization, and standardization. With international certification, Moreroom products are more environmental-friendly and healthy, providing people with a safe and methanol-free environment.

Moreroom通过ISO 9001 | ISO 50001 | ISO 14001 | 欧盟EMAS | GREENGUARD | CCC | LEED | AEO认证，从原料进厂、生产过程监控、成品出厂所有环节的人、机、料、法各指控点都进行批量化、数据化、标准化严格控制，具备国际权威认证，产品环保健康，更加安全，能够给予人们健康、安全、无甲醇的环境。



ULTRA-REALISTIC
超逼真



TOUGHNESS
超强韧性



6+MOHS HARDNESS
6+级莫氏硬度



10+COLOR CHANNELS
10色彩通道



RICH COLORS &TEXTURE
花色丰富



FOOD GRADE SURFACE
食品级表面



WATERPROOF
抗渗



SCRATCH RESISTANT
耐划刮



RESISTANT TO HIGH
TEMPERATURES
耐高温



EASY TO CLEAN
易于清洁



HYGIENIC
卫生



100% NATURAL
100%天然




RESISTANT TO UV RAYS
防紫外线



RECYCLABLE
可循环



LIGHTWEIGHT
轻盈



RESISTANT TO BENDING
抗弯折



与我们联系

Contact Us



FOSHAN MONO BUILDING MATERIAL CO.,LTD.
MOREROOM STONE CO., LTD.

Marketing Center: No.1 Building, West Area, Green Plaza, No.129
Jihua West road, Foshan City, Guangdong, China
Manufacturing Add: No.325 National Highway, Xiadong County,
Yunfu City, Guangdong, China